

PATENT ABSTRACTS OF JAPAN

(11) Publication number : **09-244045**

(43) Date of publication of application : **19.09.1997**

(51) Int.CI. **G02F 1/1343**
G02F 1/136

(21) Application number : **08-056063** (71) Applicant : **CANON INC**


(22) Date of filing : **13.03.1996** (72) Inventor : **INOUE SHUNSUKE**
OKITA AKIRA

(54) LIQUID CRYSTAL DISPLAY DEVICE AND ITS PRODUCTION

(57) Abstract:

PROBLEM TO BE SOLVED: To make it possible to increase a contrast, to decrease the variations of many pixels and to reduce a manufacturing cost by forming the same electrode layer as the pixel electrodes of an image display section on the bonding pads of peripheral circuits as well.

SOLUTION: The pixel electrodes 109 are disposed not only in the pixel parts but on the bonding pads 105 as well and are electrically connected via openings 111 on the pads. ITO films are most frequently used as the pixel electrodes 109. Al-Si films are adequate, for example, for the drain electrodes 105b of TFTs and the bonding pads 105c. The improvement of the ohmic property with the ITO films is executed by depositing films of, for example, titanium nitride, titanium, etc., on the Al-Si surfaces. Hydrogenation is executable after all of the stages to induce the damage of dry etching, etc., are ended in this stage and, therefore, the recovery and removal of the damage are embodied with good reproducibility. Since through-holes and the openings 111 of the pads are executable by the same stage, the production stages are simplified.



LEGAL STATUS

[Date of request for examination] 13.11.1998

[Date of sending the examiner's decision of rejection] 20.06.2000

[Kind of final disposal of application
other than the examiner's decision
of rejection or application
converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C) 1998,2003 Japan Patent Office

BEST AVAILABLE COPY

일본공개특허공보 평09-244045호(1997.09.19) 1부.

[첨부그림 1]

(10) 日本国特許庁 (JP) (11) 公開特許公報 (A) (12) 特許出願公開番号
特開平9-244045
(13) 公開日 平成9年(1997)9月18日

(61) Inv.Cl.° 通考番号 优先権番号 F1
G02F 1/1343 1/136 1/1343
1/138 500 1/136 500
技術表示加算


(21) 出願番号		(22) 出願日		(23) 代理人		(24) (実質の名前) 製品表示装置およびその製造方法	
特開平9-56068		平成9年(1997)3月13日		けり出版人 000001007 キヤノン株式会社 東京都大田区下丸子3丁目30番2号		けり出版人 000001007 キヤノン株式会社 東京都大田区下丸子3丁目30番2号	
				井上 敏輔 東京都大田区下丸子3丁目30番2号キヤノン株式会社内		井上 敏輔 東京都大田区下丸子3丁目30番2号キヤノン株式会社内	

(14) (実質の名前) 製品表示装置およびその製造方法

(57) (実物)

(課題) 製品表示装置のスイッチング部子の構造を向上し、さらに部品コストを下げる。

(解決手段) スイッチング部子111を複数の面を示す部品と、前記面を元に信号を出力する屈曲部111と、前記一方の基板101と、前記一方の基板101に対応して前記111を備えた他方の基板114と、前記一方の基板101と前記他方の基板114で構成した部品とを有する製品表示装置の製造方法において、前記基板部品の基板部109と同一の電極層109を、前記屈曲部111のボンディングパッド109上にも形成する。



6-1

6-1